

접수번호 : 24-021252-01-1  
(Receipt No.)



# 안전인증서

## Safety Certificate

안전인증번호 : SU10509-24008  
(Certificate No.)

제조업자/수입업자명 : SuZhou MEAN WELL Technology Co., Ltd.  
(Manufacturer/importer)

주소 : No.269, ChangPing Road, Huangdai Town, Xiangcheng District, Suzhou, China  
(Address)

제품명 : 직류전원장치(AC/DC Switching Adaptor)  
(Product)

기본모델명 : NGE90I55  
(Basic Model)

파생모델명 : See the attachment 2  
(Series Model)

정격/안전기준상의 모델구분 : 100-240 V~, 50/60 Hz, 1.8-0.9 A  
(Rating) (Output: 55 Vdc, 1.64 A, 90.2 W)

시험기준 : KC62368-1(2021-08)  
(Standard)

본 인증서는 제조국명 : 중국  
제조업자명 : SuZhou MEAN WELL Technology Co., Ltd.  
제조공장의 주소 : No.269, ChangPing Road, Huangdai Town, Xiangcheng District, Suzhou, China  
의 제품에만 해당함

「전기용품 및 생활용품 안전관리법 시행규칙」 제9조제2항, 제4항, 제10조제2항 또는 제15조제2항에 따라 안전인증서를 발급합니다.

We Issue This Safety Certificate for the above appliances in accordance with the Article 9(2),9(4),10(2) or 15(2) of the Enforcement Rule of the Electrical Appliances and Consumer Products Safety Control Act.

2024 년 05 월 09 일  
Year month day

한국산업기술시험원장  
KOREA TESTING LABORATORY



\* 이 인증서는 「전기용품 및 생활용품 안전관리법 시행규칙」에 따른 제품의 안전성 확인에 한정된 것이며, 그 밖의 다른 법률이 적용되는 제품의 경우에는 해당 법률에 따라 추가로 인증·허가 등을 받아야 합니다.

첨부서류

1. 전기용품의 안전관리부품 및 재질목록(List of Critical Components)
2. 기본모델·파생모델의 내용 (Descriptions of the basic and series model)
3. 안전인증의 변경 현황 (Revisions Status)

□ 첨부 1 : 전기용품의 안전관리부품 및 재질목록  
List of Critical Components

부품명(회로기호) Component(Part no.)	제조사(상표명) Manufacturer(Brand)	모델명(형식) Model(Type)	정격 또는 특성 Rating or Characteristics	인증마크 Tested by
Plastic Enclosure	SABIC JAPAN L L C	940(f1), 945(GG)	PC, V-0, 120 °C, min. 2.0 mm thick.	UL
(Alternate)	Sabic Innovative Plastics US L L C	940(f1)(gg*), 945(GG)	PC, V-0, 120 °C, min. 2.0 mm thick	UL
(Alternate)	Sabic Innovative Plastics B V	940(f1)(gg*), 945(GG)	PC, V-0, 120 °C, min. 2.0 mm thick	UL
(Alternate)	LG CHEM LTD	LUPOY, GP1006F(f1), GP1006F(m)(#) (f1)	PC, V-0, 110 °C, min. 2.0 mm thick.	UL
(Alternate)	LG CHEM LTD	LUPOY, EF1006F(m)(f1), EF1006F(m)(f2)	PC, V-0, 120 °C, min. 2.0 mm thick.	UL
PCB	SuZhou WuTong Electronics Co Ltd	GS-4	V-0, 130 °C	UL
(Alternate)	Interchangeable	Interchangeable	Min. V-1, Min. 130 °C	UL
Fuse (FS1)	Suzhou Walter Electric Co., Ltd.	TSC+P	T3,15 A, 250 V~	VDE
(Alternate)	Conquer Electronics Co., Ltd.	UDA-A(Pigtail type)	T3,15 A, 250 V~	VDE
X Capacitor (C1) (Optional)	LIOW GU ELECTRONICS INDUSTRY CO LTD	GS-L	Max. 0.68 uF, min. 250 V~, 40/110/56, X1 or X2	ENEC
(Alternate)	Joey Electronics (Dong Guan) Co., Ltd.	MPX	Max. 0.68 uF, min. 250 V~, 40/110/21, X1 or X2	VDE
(Alternate)	CHIEFCON ELECTRONICS CO LTD	CKX	Max. 0.68 uF, min. 250 V~, 55/110/56, X1 or X2	ENEC
Bridge Capacitor (C31, C32) (Optional)	Sichuan Teruixiang Technology International Co Ltd	TRX	Max. 1000 pF, min. 250 V~, min. 25/125/21, Y1	ENEC
(Alternate)	ANSHAN KEIFAT ELECTRONIC CERAMIC TECHNICAL CO LTD	SYW	Max. 1000 pF, min. 250 V~, min. 25/125/21, Y1	ENEC
(Alternate)	ANSHAN KEIFAT ELECTRONIC CERAMIC TECHNICAL CO LTD	CT7	Max. 1000 pF, min. 250 V~, 40/125/21, or 25/125/21, Y1	VDE
Bridge Capacitor (C33, C34)	Sichuan Teruixiang Technology International Co Ltd	TRX	Max. 470 pF, min. 250 V~, 25/125/21, Y1	ENEC

부품명(회로기호) Component(Part no.)	제조사(상표명) Manufacturer(Brand)	모델명(형식) Model(Type)	정격 또는 특성 Rating or Characteristics	인증마크 Tested by
(Alternate)	ANSHAN KEIFAT ELECTRONIC CERAMIC TECHNICAL CO LTD	SYW	Max. 470 pF, min. 250 V~, 25/125/21, Y1	ENEC
(Alternate)	ANSHAN KEIFAT ELECTRONIC CERAMIC TECHNICAL CO LTD	CT7	Max. 470 pF, min. 250 V~, 40/125/21, or 25/125/21, Y1	VDE
Photo Coupler (U3, U4)	Lite-On Technology Corporation	LTV-1008	Reinforced insulation	VDE
(Alternate)	VISHAY SEMICONDUCTOR GMBH	TCLT1008	Reinforced insulation	VDE
(Alternate)	Ct Microelectronics Far East Ltd	CT1018(V)(T)-W	Reinforced insulation	VDE
(Alternate)	Everlight Electronics Co., Ltd.	EL1018	Reinforced insulation	VDE
Transformer (T1)	MEAN WELL Enterprise Co., Ltd.	TF5911 for 12V out, TF5912 for 15V, 18V out, TF5914 for 24V out, TF5915 for 48V out, TF5916 for 55V out	Class B	Tested with appliance
Line Choke (LF1) (Optional)	MEAN WELL Enterprises Co., Ltd.	TR-732H	Rated min. 130 °C	Tested with appliance
Line Choke (LF2) (Optional)	MEAN WELL Enterprises Co., Ltd.	TR-5132A	Rated min. 130 °C	Tested with appliance
Bleeder Resistor (R1, R2)	Interchangeable	Interchangeable	Each Max. 180 KΩ , min. 1/4 W	--

유의사항 (Attention) :

1. 안전관리부품은 전기적인 안전에 직접적인 영향을 주는 부품으로서 안전인증기관이 정기공장검사 시 확인 관리 하는 사항입니다. 따라서 상기목록에 기재된 사항을 변경하거나 또는 복수등재를 원하시는 경우는 안전인증기관에 인증변경신청을 하여야 합니다.

*As the "Critical components" are parts in directly related with safety, these components shall be checked during a factory inspection by the certification body. In case of applying multiple listing or changing the items above, the certification revision shall be applied.*

2. 인증변경신청 없이 임의로 변경하는 경우는, 전기용품 및 생활용품 안전관리법 시행규칙 제 21 조제 1 항 또는 제 38 조제 1 항 규정에 의한 안전인증 취소 혹은 안전확인신고 효력상실 사유가 됨을 유의하시기 바랍니다.

*The Safety Certification will be cancelled under the Article 21(1), 38(1) of the Enforcement Rule of the Electrical appliances and Consumer Products Safety Control Act if the contents of the Certification is altered without our authorization.*

□ 첨부 2 : 기본모델 · 파생모델의 내용  
Description of the basic and series model

파생모델명 Derivative model	기본모델과의 차이점 Differences between the basic and derivative model(s)
NGE90KR55	Same as basic model except model name.
NGE90I15	Same as basic model except model name, transformer secondary wiring and output ratings: 15V, 5.5A, 82.5W.
NGE90KR15	Same as basic model except model name, transformer secondary wiring and output ratings: 15V, 5.5A, 82.5W.
NGE90I18	Same as basic model except model name, transformer secondary wiring and output ratings: 18V, 5A, 90W.
NGE90KR18	Same as basic model except model name, transformer secondary wiring and output ratings: 18V, 5A, 90W.
NGE90I24	Same as basic model except model name, transformer secondary wiring and output ratings: 24V, 3.75A, 90W.
NGE90KR24	Same as basic model except model name, transformer secondary wiring and output ratings: 24V, 3.75A, 90W.
NGE90I48	Same as basic model except model name, transformer secondary wiring and output ratings: 48V, 1.875A, 90W.
NGE90KR48	Same as basic model except model name, transformer secondary wiring and output ratings: 48V, 1.875A, 90W.
NGE90I12	Same as basic model except model name, transformer secondary wiring and output ratings: 12V, 6.25 A, 75W.
NGE90KR12	Same as basic model except model name, transformer secondary wiring and output ratings: 12V, 6.25 A, 75W.
제품특기사항 및 시험조건 Remarks & Test conditions	
<p>1. Review Ref. No.: 24-021252-01-2 - DEKRA Ref. No.: 4917550.01</p> <p>2. Product Description: - Measured power consumption: 97.05 W - Insulation class: Class II - Protection against Ingress of water: IP21 - Mass of equipment (kg): max. 0.24 kg</p>	
<p>□ 본 제품의 검토내용에 관하여 문의하실 사항이 있으시면 아래 연락처로 문의하시기 바랍니다. 검토담당자 / 연락처 : 인증사업본부 인증융합센터 장 재용 / 055-791-3305</p> <p>□ <i>If you have any question on product review, please contact the person below :</i> <i>Job holder: Certification Business Division, Certification Convergence Center, J.Y.Jang / +82 55 791 3305</i></p>	

FP511-05

**첨부 3 : 안전인증의 변경 현황**  
Revisions Status

변경발급 내용 Contents of Certificate Revisions
Not applicable

FP511-06

첨부 : 제품사진  
Photographs



